

MULTISPORT Range SUPER PRO Readability 160 m

BASKET BALL - HANDBALL - VOLLEYBALL - TENNIS - TABLE TENNIS - BADMINTON - FUTSAL - RINK HOCKEY
 IN LINE HOCKEY - ICE HOCKEY - UNIHOCKEY / FLOORBALL - NETBALL - BOXING - FREE MODE

452 MF 3123-123

PARKER 28... • 1	108 3 > 139	CALABRIA 28... • 1
PIETRUS 13... • 10	FRANCE ITALIE	BASILE 13... • 10
GELABALE 37... • 4	5 : 19:46 : 3	GALANDA 37... • 4
WEIS 45... • 23	15 1:23 34 0:58	SORAGNA 45... • 23
FAUTHOUX 15... • 2	8 2:57 47 3:09	MARCONATO 15... • 2
RIGAUDEAU 8... • 15	20 3:41 96 4:00	POZZECCO 8... • 15
JULIAN 59... • 7		RIGHETTI 59... • 7
DIARRA 34... • 19		MANCINELLI 34... • 19
SCHMITT 20... • 6		BULERRI 20... • 6
DIAM 47... • 24		MORDANTE 47... • 24
ARBERISTO 62... • 18		CHIACIG 62... • 18
GIFFA 96... • 3		GIGLI 96... • 3

(non contractual picture)



Composition

- 1 scoreboard made of 6 modules
- 2 control consoles, 1 start/stop timer console
- 1 PC keyboard
- 2 carrying cases for control consoles
- 3 mains cables
- Junction box and transmission cables (for cable controlled version)
- Operating and installation instructions

Description

Use:	Indoor
Transmission:	Cable. Radio transmission (868 MHz) as an option.
Readability:	160m, angle >160°
Dimensions:	6900 x 2500 x 90mm
Weight:	276 kg
Power supply:	230V / 50-60Hz
Protection:	Unbreakable matt polycarbonate front face (DIN 18032-3)
Horn:	2x integrated horns, total = 119dB at 1m
Mains cable (supplied):	3x20 m – Type: 230V, 3G, 0.75 mm ²
Cable controlled:	For cable controlled models or radio controlled models with cable set: Junction Box + 50 m transmission cable (scoreboard/junction box) – Type: phone cable 2 pairs 6/10th + 10 m transmission cable DIN/DIN (junction box/console)

Power consumed: 1092 VA

Display functions

Score:	2 x 3 red LED digits (30 cm)
Period:	1 green LED digit (25 cm)
Team names:	20 yellow LED alphanumerical characters (16 cm)
Moving messages (Ads/Sponsor):	1000 characters
Ball possession:	2 red LED arrows
Timer/Rest period:	4 white LED digits (30 cm) + blinking points
Team fouls (BB) or sets (VB, T, TT...):	2 yellow LED digits (25 cm)
Time out (BB, HB, VB) /	
No. of exclusions (HB):	2 x 3 green LED points
Excluded player (HB)/	
Last penalized player (BB)/	
Set result for home team (VB, T, TT...):	6 x 2 yellow LED digits (20 cm)
Penalty timer (HB)/Time-out timer (BB)/ No. of individual fouls for last penalized player (BB)/	
Set result for guest team (VB, T, TT...):	6 x 3 red LED digits (20 cm) + blinking points
Player names (2 modules):	10 yellow LED alphanumerical characters (12 cm) per player (12)
Player number (2 modules):	2 yellow LED digits (12 cm) per player (12)
Individual fouls (BB) (2 modules):	5 yellow LED points + 1 red LED point per player (12)
Individual points (2 modules):	2 red LED digits (12 cm) per player (12)
Day Time:	When the scoreboard is not in use

Control consoles

2 consoles: (340 x 175 x 60 mm) with LCD screen with 2 lanes of 20 characters (9mm high)

- **Main console:** management of the main functions
- Control console for **individual fouls and points**

1 Start/stop timer console: 145 x 150 x 40 mm for timer, time out, horn

1 Keyboard Entering team and players names + moving messages (option)

1 charger (radio): Hold the consoles in charge when there are not in use. (Autonomy max 16 h)

Connection plugs: DIN between the consoles

USB Port: For program update or connect PC keyboard

Programme: 14 sport disciplines + « Free mode » to create your own sport discipline or for additional sports (wrestling, Pelota...)

Multilingual Programme

Options

TV Interface (RS 485):	Data transmission for TV broadcasting
Sound Interface:	Connection with sport hall sound system - Horn sound amplifier
DCF or GPS Antenna:	For accurate time synchronisation
Cable set:	Cable mode for radio controlled scoreboard
Precision Time Interface:	Connection with electronic whistle
Pair of shot-clocks:	Attack timer with or without main time repeater
Led Strips:	Electric light to be installed behind the backboard
MPA:	Ball possession indicator
Netbook:	With special programme for teams management

452 MF 3123-123_GB_A.doc