

2 x 3 red LED digits (30 cm)

20 yellow LED alphanumerical characters (16 cm)

4 white LED digits (30 cm) + blinking points

2 yellow LED digits (12 cm) per player (12)

14 sport disciplines + « Free mode » to create your own sport discipline or for

Connection with sport hall sound system - Horn sound amplifier

5 yellow LED points + 1 red LED point per player (12)

When the scoreboard is not in use

6 x 2 yellow LED digits (20 cm)

1 green LED digit (25 cm)

1000 characters

Excluded player (HB)/ Last penalized player (BB)/Set result for home team (VB. T. TT...):

2 consoles: (340 x 175 x 60 mm) with LCD screen with 2 lanes of 20 characters (9mm high)

Entering team and players names + moving messages (option)

1 charger (radio): Hold the consoles in charge when there are not in use. (Autonomy max 16 h)

Data transmission for TV broadcasting

Cable mode for radio controlled scoreboard

Attack timer with or without main time repeater

Electric light to be installed behind the backboard

With special programme for teams management

For accurate time synchronisation

Connection with electronic whistle

Ball possession indicator

Set result for guest team (VB, T, TT...): 6 x 3 red LED digits (20 cm) + blinking points

Penalty timer (HB)/Time-out timer (BB)/ No. of individual fouls for last penalized player (BB)/

Team fouls (BB) or sets (VB, T, TT...): 2 yellow LED digits (25 cm)

Time out (BB, HB, VB) /No. of exclusions (HB): 2 x 3 green LED points

Main console: management of the main functions

1 Start/stop timer console: 145 x 150 x 40 mm for timer, time out, horn

For program update or connect PC keyboard

additional sports (wrestling, Pelota...)

Control console for individual fouls and points

2 red LED arrows

MULTISPORT Range SUPER PRO Readability I60 m

BASKET BALL – HANDBALL – VOLLEYBALL – TENNIS – TABLE TENNIS – BADMINTON – FUTSAL – RINK HOCKEY IN LINE HOCKEY– ICE HOCKEY · UNIHOCKEY / FLOORBALL – NETBALL – BOXING – FREE MODE

452 MF 3123-2





Composition

1 scoreboard made of 4 modules 2 control consoles, 1 start/stop timer console 1 PC keyboard 2 carrying cases for control consoles 3 mains cables Junction box and transmission cables (for cable controlled version) Operating and installation instructions

Description

Indoor	
Cable or Radio transmission (868 MHz) as an option	
160m, angle >160°	
4400 x 2500 x 90mm	
176 kg	
230V / 50-60Hz	Power consumed: 543 VA
Unbreakable matt polycarbonate front face (DIN 18032-3)	
2x integrated horns, total	120dB at 1m
3x25 m – Type: 230V, 3G, 0.75 mm²	
For cable controlled mode	els or radio controlled models with cable set:
Junction Box + 50 m transmission cable (scoreboard/junction box) –	
Type: phone cable 2 pairs 6/10th + 10 m transmission cable DIN/DIN (junction	
box/console)	
	160m, angle >160° 4400 x 2500 x 90mm 176 kg 230V / 50-60Hz Unbreakable matt polyca 2x integrated horns, total 3x25 m – Type: 230V, 3G, For cable controlled mode Junction Box + 50 m trans Type: phone cable 2 pairs

F COM 18 A

Display functions

Moving messages (Ads/Sponsor):

Central module:

Team names:

Day Time:

Ball possession:

Bottom module :

Lateral modules :

-

1 Kevboard

USB Port:

Programme:

Options

Cable set:

Led Strips:

Netbook:

MPA:

Player number (2 modules):

Control consoles

Multilingual Programme

TV Interface (RS 485):

DCF or GPS Antenna:

Pair of shot-clocks:

Precision Time Interface:

Sound Interface:

Individual fouls (BB) (2 modules):

Connection plugs: DIN between the consoles

Timer/Rest period:

Score:

Period:

452 MF 3123-2 GB A