

OUTDOOR- Readability I20 m

SOCCER – RUUBY – HELD HOCKEY

FRB AD





(non binding picture)

Composition

1 scoreboard (made of 1 module)

1 control console

1 carrying case for control console

1 PC-Keyboard

1 mains cable

Operating and installation instructions

Technical description

Use: Outdoor

Transmission :Radio (868 MHz) or cableReadability :120m, angle >160°Dimensions :2000 x 1000 x 90 mm

Weight: 38 kg

Power supply: 230V / 50-60Hz Power consumed: 192 VA

Protection: unbreakable mat polycarbonate front face (DIN 18032-3)

Mains cable (supplied): 5m (socket not supplied) – Type: 230V, 3G, 0.75 mm²

Cable controlled: for cable controlled models or radio controlled models with cable set

Junction box + 50m transmission cable (scoreboard / junction box) — Type: phone cable 2 pairs 6/10th + 10m transmission cable DIN/DIN

(junction box / console)

Installation: on I-Beams(adjustable fixing) or wall-mounted (with clamps supplied)

Brightness: adjustable from the control console

Display functions

Score: 2 x 2 red LED digits (25 cm)

Timer / Rest period : 4 red LED digits (25 cm) + 2 blinking points **Team names:** 15 red LED alphanumerical characters (16 cm)

Moving messages (Ads/Sponsor): 1000 characters

Day time: when the scoreboard is not in use

(switched off at night)

Control consoles

1 console: (340 x 175 x 60 mm) with LCD-screen with 2 lanes of 20 characters (9mm high)

1 charger (radio): Hold the console in charge when not in use (Autonomy max. 16h)

USB Port: For program update or connect PC Keyboard
Programme: 3 sport disciplines: Soccer, Rugby, Field Hockey

Multilingual programme

Options

TV Interface (RS 485): Data transmission for TV broadcasting

Sound Interface: Connection with sound system - Horn sound amplifier

DCF or GPS Antenna: For accurate time synchronisation

Cable set:Cable mode for radio controlled scoreboard **Advertising panels:**Black panels (advertising stickers on demand)

 $FRBAD_GB_A$