

MULTISPORT SHOT-CLOCKS Readability 110 m
BASKET BALL

SC24 TIMER PRO



(non contractual pictures)



Composition

- 2x display units
- 1 control console
- 1 carrying case for control console
- 2 mains cable
- 2x junction boxes and transmission cables
- Operating and installation instructions

Description (per display unit)

- Use:** Indoor
- Transmission:** Radio (868 MHz) or cable. Work only with STRAMATEL Multisport scoreboard
- Readability:** 110m, angle >160°
- Dimensions:** 770 x 570 x 90mm
- Weight:** 10 kg
- Power supply:** 230V / 50-60Hz
- Power consumed:** 89 VA
- Protection:** Unbreakable matt polycarbonate front face (DIN 18032-3)
- Integrated Horn:** 115dB at 1m
- Mains cable (supplied):** 2x25 m – Type: 230V, 3G, 0.75 mm²
- Cable controlled model:** Junction Box + 2 x 25 m transmission cable (scoreboard/junction box) – Type: DIN/DIN + 25 m transmission cable (junction box/main junction box) Type: phone cable 2 pairs 6/10th

Display functions (per display unit)

- Shot-clock:** 2 red LED digits (20 cm)
- Game clock repeater:** 4 white LED digits (16 cm) + blinking points
- 24/14s violation:** 1 red LED point

Control consoles

- 1 console: (145 x 150 x 40 mm) with LCD screen with 1 lane of 20 characters (9mm high)
 - Shot-clock controller

WORK ONLY WITH STRAMATEL MULTISPORT SCOREBOARD

Options

- Led Strip:** Electric light to be installed behind the backboard, connected with the 24 second shot clocks, synchronised with the main timer to light up at the end of each period

