

MULTISPORT SHOT-CLOCKS Readability 100 m

BASKET BALL

SC 24 Eco



(non contractual picture)



Composition

- 2 electronic display boards
- 1 control console,
- 1 horn
- 1 carrying case for control console
- 2 main cables
- 2 polycarbonate stands (Floor installation)
- Operating and installation instructions

Description

- Use:** Indoor
- Transmission:** Cable – work independently from main scoreboard or connected with a portable STRAMATEL scoreboard Model MTop.
- Readability:** 100m, angle >160°
- Dimensions:** 500 x 300 x 65 mm
- Weight:** 2,5 kg per unit
- Power supply:** 230V / 50-60Hz 0,2A
- Power consumed:** 40 VA
- Protection:** Unbreakable matte polycarbonate front face (DIN 18032-3)
- External Horn:** 96dB at 1m
- Transmission cable:** 25 m + 35 m – Type: phone cable, 4 wires, 0.60mm<sup>2</sup>  
2 + 3m – DIN /DIN (connection Horn / Control console)
- Mains cable:** 1 x 2 – Typ: 230V, 3G, 0.75 mm<sup>2</sup>

Display functions

- 24/14 second attack timer: 2 red LED digits (23 cm) per display
- Timer Stop: 1 red LED dots (5 cm) per display

Control consoles

- 1 console: (145 x 150 x 40 mm) with LCD screen
- 1 carrying case: for control console (270 x 200 x 50 mm)
- WORK INDEPENDANTLY FROM A MAIN SCOREBOARD OR WITH A PORTABLE SCOREBOARD M-Top

Options

- Led Strip:** Electric light to be installed behind the backboard, connected with the 24 second shot clocks, synchronised with the main timer to light up at the end of each period.

