

MULTISPORT SHOT-CLOCKS Readability 100 m

BASKET BALL

SC 24



(non contractual picture)



Composition

- 2 electronic display boards
- 1 control console,
- 1 carrying case for control console
- 2 main cables
- 2 polycarbonate stands (Floor installation)
- Operating and installation instructions

Description

- Use :** Indoor
- Transmission :** Radio (868 MHz) or cable – work ONLY with STRAMATEL main scoreboard
- Readability :** 100m, angle >160°
- Dimensions :** 500 x 300 x 65 mm
- Weight :** 2,5 kg per unit
- Power supply :** 230V / 50-60Hz
- Power consumed:** 33 VA
- Protection :** Unbreakable matte polycarbonate front face (DIN 18032-3)
- Integrated Horn :** 96dB at 1m
- Mains cable (supplied) :** 2 x 25 m – Typ: 230V, 3G, 0.75 mm²

Display functions

- 24/14 second attack timer:** 2 red LED digits (23 cm) per display
- Timer Stop:** 1 red LED dots (5 cm) per display

Control consoles

- 1 console:** (145 x 150 x 40 mm) with LCD screen
 - 1 carrying case:** for control console (270 x 200 x 50 mm)
- WORK ONLY WITH A STRAMATEL ELECTRONIC SCOREBOARD**

Options

- Led Strip:** Electric light to be installed behind the backboard, connected with the 24 second shot clocks, synchronised with the main timer to light up at the end of each period.

Installation support frame (for installation behind the Basket Ball Backboards)

