

MULTISPORT SHOT-CLOCKS Readability 100 m

BASKET BALL

**SCX 24**



(non contractual picture)



**Composition**

- 2 electronic display boards
- 1 control console,
- 1 carrying case for control console
- 2 main cables
- 2 polycarbonate stands (Floor installation)
- Operating and installation instructions

**Description**

- Use :** outdoor
- Transmission :** Radio (868 MHz) or cable – work ONLY with STRAMATEL main scoreboard
- Readability :** 100m, angle >160°
- Dimensions :** 500 x 300 x 65 mm
- Weight :** 2,5 kg per unit
- Power supply :** 230V / 50-60Hz
- Power consumed:** 33 VA
- Protection :** Unbreakable mat polycarbonate front face (DIN 18032-3)
- Integrated Horn :** 96dB at 1m
- Mains cable (supplied) :** 2 x 25 m – Typ: 230V, 3G, 0.75 mm<sup>2</sup>

**Display functions**

- 24/14 second attack timer:** 2 red LED digits (23 cm) per display
- Timer Stop:** 1 red LED dot (5 cm) per display

**Control consoles**

- 1 console:** (145 x 150 x 40 mm) with LCD screen
- 1 carrying case:** for control console (270 x 200 x 50 mm)

**WORK ONLY WITH A STRAMATEL ELECTRONIC SCOREBOARD**

**Options**

- Led Strip:** Electric light to be installed behind the backboard, connected with the 24 second shot clocks, synchronised with the main timer to light up at the end of each period.

**Installation support frame** (for installation behind the Basket Ball Backboards)

